



**TOWER<sup>®</sup>**  
SEALANTS

# CAULKS & SEALANTS

## TOWER TECH<sup>2</sup>™

**TOWER TECH<sup>2</sup>** Elastomeric Acrylic Urethane Sealant has exceptional strength and durability. Superior adhesion to most substrates with more than 800% elongation. It's internally plasticized, has reduced dirt pickup, won't yellow and prevents paint shiners. Forms a permanently flexible, airtight, water-resistant seal in gaps up to 2" wide.



PRODUCT ATTRIBUTE	TOWER TECH <sup>2</sup>
ASTM C-920 TESTING	EXCEEDS
ASTM C-834 TESTING	EXCEEDS
FED SPEC TT-S-00230C	EXCEEDS
AAMA 808.3	PASSES
MAXIMUM ELONGATION	800%
PAINTABLE W/WATERBORNE AND OILS	YES
PAINT OVER TIME	4 TO 6 HOURS
MAX. JOINT WIDTH	UP TO 2"
VACUUM FILLED TUBES	YES
PROVIDES MILDEW RESISTANT SEAL	YES
WARRANTY	LIFETIME
INDOOR/OUTDOOR USE	YES
NATIONWIDE VOC COMPLIANT	YES <1.2%
SHELF LIFE	24 MONTHS
AVAILABLE COLORS	WHITE, BLACK, ALMOND, ALUMINUM GRAY, BRONZE, LIMESTONE, OFF-WHITE, PINE GREEN, REDWOOD, REDWOOD TAN, STONE, TAN, WOODTONE & CLEAR

SASHCO BIG STRETCH	SW SHER-MAX
EXCEEDS	MEETS
EXCEEDS	MEETS
EXCEEDS	MEETS
NO	NO
500%	N/A
YES, BUT OILS MUST DRY 1 WEEK	YES
4 TO 48 HOURS	4 HOURS
UP TO 2"	1/2"
NO	NO
YES	YES
LIFETIME	LIFETIME
YES	YES
YES <1.5%	YES <0.5%
12 MONTHS	12 MONTHS
WHITE, CLEAR, & COLORS	WHITE & CLEAR

## The TOWER TECH<sup>2</sup> Advantage

- ✓ High elongation sealant
- ✓ Can span joint widths up to 2"
- ✓ Will not discolor or bleed through paint
- ✓ Exceeds ASTM C-920, C-834, TT-S-00230C & AAMA 808.3
- ✓ Low VOC
- ✓ 20 FL. OZ. Sausages available
- ✓ Lifetime Limited Warranty